

## Floor Polishers and Burnishers

### Propane Burnisher

- Electric Clutch
- Emission Guard
- Catalytic Muffler
- Easy to Use
- Productivity:  
Powerful engines maintain speed under heaviest loads. Super grip pad driver face reduces pad expansion and increases pad life.
- Safety:  
Super clean catalytic converter aids in improving air quality. Low oil alert system protects engine.
- 10+3+1 = Dustbane Warranty



SPECIFICATIONS	21"	24"	27"
ENGINE	13 HP Kawasaki	13 HP Kawasaki	17 HP Kawasaki
STARTING SYSTEM	12 V Battery	12 V Battery	12 V Battery
BURNISHING PATH	21"	24"	27"
IGNITION SYSTEMS	Electronic	Electronic	Electronic
FUEL TANKS	20 lbs	20 lbs	20 lbs
CATALYTIC MUFFLER	Included	Included	Included
LOW OIL SHUT-DOWN	Included	Included	Included
ELECTRICAL FUEL LOCK-OFF	12 V Start	12 V Start	12V Start
VACUUM FUEL LOCK-OFF	110V Start	110 V Start	110V Start
CODE	19314	19317	19318

### Integra TX Series

Dustbane's INTEGRA TX floor polishers and UHS burnishers are designed to provide maximum performance and durability. Look for the following features :

- New technology triax
- New easy-to-operate trigger
- New rotationally molded base
- Conversion kit for old to new trigger assembly
- New 10-year brush cover warranty
- Adjustable wheel
- 6 models to choose from
- New bumper
- 10+3+1 = Dustbane Warranty



SPECIFICATIONS	175 RPM SINGLE SPEED	175 RPM-320 RPM DUAL SPEED	1500 RPM UHS	750-1500 RPM DUAL SPEED UHS	2000 UHS C/W DUST COLLECTOR
MOTOR	AC capacitor	Permanent magnet	Permanent magnet	Permanent magnet	Permanent magnet
HORSEPOWER/WATTS	1.0 hp (745 watts)	1.5 hp (1118 watts)	1.5 hp (1118 watts)	1.5 hp (1118 watts)	1.5 hp (1118 watts)
VOLT	115 AC	115 AC	115 AC	115 AC	115 AC
AMPS	14 amps	10 amps <sup>Low</sup> 13 amps <sup>High</sup>	13 amps	8 amps <sup>Low</sup> 12 amps <sup>High</sup>	13 amps
MOTOR RPM	1740 rpm	3200 rpm	1500 rpm	1500 rpm	2000 rpm
NOISE LEVEL	55dB(A)	60dB(A) <sup>Low</sup> 63dB(A) <sup>High</sup>	58dB(A)	58dB(A) <sup>Low</sup> 61dB(A) <sup>High</sup>	61dB(A)
GEARBOX TYPE	3 idler - ratio 10:1	3 idler - ratio 10:1	Direct drive	Direct drive	Direct drive
SAFETY CORD LENGTH	14/3 - 50' (15.2 m)	14/3 - 50' (15.2 m)	14/3 - 75' (22.9 m)	14/3 - 75' (22.9 m)	14/3 - 75' (22.9 m)
NET WEIGHT	85 - 90 lbs (38.6 - 40.8 kg)	80 - 85 lbs (36.3 - 38.6 kg)	70 lbs (31.8 kg)	70 lbs (31.8 kg)	70 lbs (31.8 kg)
SHIPPING WEIGHT	100 - 105 lbs (45.5 - 47.6 kg)	95 - 100 lbs (43.1 - 45.5 kg)	88 lbs (39.9 kg)	88 lbs (39.9 kg)	88 lbs (39.9 kg)
SIZE	17" or 19" (43.2 or 48.3 cm)	17" or 19" (43.2 or 48.3 cm)	20" (50.8 cm)	20" (50.8 cm)	20" (50.8 cm)
CSA APPROVED	Yes	Yes	Yes	Yes	Yes
DRIVE PAD (INCLUDED)	No drive pad	Standard drive pad	Flex drive pad	Flex drive pad	Flex drive pad
CODE	17": 19910    19": 19911	17": 19914    19": 19915 17" <sup>LA</sup> : 19934    19" <sup>LA</sup> : 19935	19917	19916	19918